Versions		595C	595C Pista	595C Turismo	595C Competizione
WEIGHT	Kerb weight [Kg] (MTA Transmission)	1075 (1085)	1075 (1085)	1075 (1085)	1090 (1090)
	Weight-to- power ratio [kg/hp]	7.4	6.7	6.5	6.1
DIMENSIONS	Length [mm]	3660	3660	3660	3660
	Width [mm] (with ext. mirrors)	1627 (1893)	1627 (1893)	1627 (1893)	1627 (1893)
	Height [mm]	1485	1485	1485	1485
	Wheelbase [mm]	2300	2300	2300	2300
	Front overhang [mm]	770	770	770	770
	Rear overhang [mm]	590	590	590	590
	Front track [mm]	1415	1415	1415	1415
	Rear track [mm]	1408	1408	1408	1408
VOLUMES AND CAPACITY	Seats	4	4	4	4
	Luggage compartment [I]	185	185	185	185
	Tank [I]	35	35	35	35
ENGINE	Fuel type	Petrol	Petrol	Petrol	Petrol
	Required fuel	95 RON EN 228			
	Cylinders	4	4	4	4
	Bore and stroke [mm]	72.0 x 84.0	72.0 x 84.0	72.0 x 84.0	72.0 x 84.0
	Displacement [cc]	1368	1368	1368	1368
	Compression ratio	9.8 : 1	9.8 : 1	9.0 : 1	9.0:1
	Maximum power [hp(kW) @ rpm]	145 (107) @ 5500	160 (118) @ 5500	165 (121) @ 5500	180 (132) @ 5500
	Maximum torque [Nm @ rpm]	206 @ 3000	230 @ 3000	230 @ 3000	250 @ 3000
	Turbocharger	IHI RHF3-P	IHI RHF3-P	GARRETT GT 1446	GARRETT GT 1446

	Air filter	Standard	BMC high	BMC high	BMC high
	All litter	Standard	performance	performance	performance
	Exhaust	Abarth exhaust	Dual Mode	Abarth exhaust	Dual Mode
	system	with chrome	Record Monza	with chrome	Record Monza
	0,000	dual tips	exhaust with 4	dual tips	exhaust with 4
			tips		tips
DRIVELINE	Traction	FWD	FWD	FWD	FWD
	Туре	Mechanical 5-	Mechanical 5-	Mechanical 5-	Mechanical 5-
	, ,	speed	speed	speed	speed
	Transmission ratios				
	1st	3.538	1:3.909	1:3,909 (3,545 MTA)	1:3,909 (3,545 MTA)
	2nd	2.060	1:2.238	1:2.238	1:2.238
	3rd	1.404	1:1.520	1:1.520	1:1.520
	4th	1.000	1:1.156	1:1.156	1:1.156
	5th	0.713	1:0.872	1:0.872	1:0.872
	Reverse	1:3.909	1:3.909	1:3.909	1:3.909
ELECTRICAL SYSTEM	Battery	250 A / 50 Ah	250 A / 50 Ah	250 A / 50 Ah	250 A / 50 Ah
SUSPENSIONS	Front	McPherson with anti-roll bar	McPherson with anti-roll bar	McPherson with anti-roll bar	McPherson with anti-roll bar
	Shock	Telescopic with	Telescopic with	Telescopic with	KONI with FSD
	absorbers	FSD valve	FSD valve	FSD valve	valve
	Rear	Torsion beam with anti-roll bar	Torsion beam with anti-roll bar	Torsion beam with anti-roll bar	Torsion beam with anti-roll bar
	Shock absorbers	Telescopic	KONI with FSD valve	KONI with FSD valve	KONI with FSD valve
BRAKING SYSTEM	Front	Floating calipers	Floating calipers	Floating calipers	BREMBO aluminium 4- piston fixed calipers
	Dimensions	Ventilated \$\phi 284 \text{ X 22 mm}\$ brake discs	Ventilated and perforated ¢284 X 22 mm brake discs	Ventilated and perforated ¢284 X 22 mm brake discs	Ventilated and perforated \$\phi305\$ X 28 mm brake discs
	Rear	Floating calipers	Floating calipers	Floating calipers	Floating calipers
	Dimensions	Solid $\phi$ 240 X 11 mm brake discs	Perforated φ240 X 11 mm brake discs	Perforated φ240 X 11 mm brake discs	Perforated φ240 X 11 mm brake discs

TYRES	Sizes and type	195/45 R16 - Summer	205/40 R17 - Summer	205/40 R17 - Summer	205/40 R17 - Summer
STEERING	Туре	Dualdrive electrically assisted power steering with "sport mode"	Dualdrive electrically assisted power steering with "sport mode"	Dualdrive electrically assisted power steering with "sport mode"	Dualdrive electrically assisted power steering with "sport mode"
PERFORMANCE	Acceleration 0-100 km/h [s] (MTA transmission)	7.8 (8)	7.3 (7.4)	7.3 (7.4)	6.7 (6.9)
	Top speed [km/h]	210	216	218	225
	CO2 [g/km] (MTA transmission)	139 (134)	139 (134)	139 (134)	139 (134)
	Combined cycle [I/100Km] (MTA transmission)	6.0 (5.8)	6.0 (5.8)	6.0 (5.8)	6.0 (5.8)
	Urban cycle [I/100Km] (MTA transmission)	7.9 (7.6)	7.9 (7.6)	7.9 (7.6)	7.9 (7.6)
	Extra-urban cycle [I/100km] (MTA transmission)	4.9 (4.7)	4.9 (4.7)	4.9 (4.7)	4.9 (4.7)
	Emissions class	Euro 6	Euro 6	Euro 6	Euro 6