

| VERSION | | 1.4 Mair 140hp MT | 1.4 Mair 140 hp AT |
|-------------------------|-------------------------------|--|--|
| WEIGHT | Curb weight [Kg] | 1050 | 1070 |
| | Weight to power ratio [Kg/cv] | 7.5 | 7.6 |
| DIMENSIONS & CAPACITIES | Length [mm/in] | 4054 | 4054 |
| | Width [mm/in] | 1740 | 1740 |
| | Height [mm/in] | 1233 | 1233 |
| | Wheelbase [mm/in] | 2310 | 2310 |
| | Front over hang | 834 (853 with license plate holder) | 834 (853 with license plate holder) |
| | Rear over hang | 910 | 910 |
| | Front Track [mm/in] | 1496 | 1496 |
| | Rear Track [mm/in] | 1503 | 1503 |
| | Approach angle [degrees] | 13.1° | 13.1° |
| ACCOMODATIONS | Seating Capacity - Front | 2 | 2 |
| | Head Room [mm/in] | 950 | 950 |
| | Legroom [mm/in] | 1096 | 1096 |
| | Shoulder Room [mm/in] | 1325 | 1325 |
| | Hip Room [mm/in] | 1320 | 1320 |
| | Seat Travel [mm/in] | 210 driver - 170 passenger | 210 driver - 170 passenger |
| | Recliner Range [degrees] | From 25 nominal, 12 forward and 22 rearward | From 25 nominal, 12 forward and 22 rearward |
| | Cargo Space [l/cu. ft.] | 140 | 140 |
| | Fuel Type | Gasoline | Gasoline |
| | Fuel Requirement | 95 RON EN 228 | 95 RON EN 228 |
| | Fuel Tank Capacity [l/gal.] | 45 | 45 |
| | Cylinders | 4 | 4 |
| | Construction | Cast Iron Block with aluminium alloy head and bedplate | Cast Iron Block with aluminium alloy head and bedplate |
| | Valve System | MultiAir 16 valves | MultiAir 16 valves |
| | Fuel Injection | Sequential, multiport, electronic, returnless | Sequential, multiport, electronic, returnless |
| | Bore x Stroke [mm] | 72.0 x 84.0 | 72.0 x 84.0 |
| | Displacement [cc] | 1368 cc | 1368 cc |
| | Compression Ratio | 9.8 : 1 | 9.8 : 1 |
| | Maximum Turbo Boost [bar] | 2.49 bar | 2.49 bar |
| | Max Power CV(kW) @ rpm | 140 (103) @ 5000 | 140 (103) @ 5000 |

| | | | |
|--------------------------|-------------------------|---|---|
| | Max Torque Nm @ rpm | 240 @ 2250 | 240 @ 2250 |
| | Max Engine Speed [rpm] | 6500 | 6500 |
| | Oil Capacity [l] | 3.8 L with dry filter | 3.8 L with dry filter |
| | Coolant Capacity [l] | LHD : 7.2L, RHD : 6.7L | LHD : 7.1L, RHD : 6.5L |
| | Emission Controls | Three-way catalytic converter | Three-way catalytic converter |
| | Stop&Start System | No | No |
| TRANSMISSION | Traction | RWD | RWD |
| | Type | Manual | Automatic |
| | Description | 6-speed manual | 6-speed automatic |
| | Gear ratios | | |
| | 1st | 4.363 | 3.538 |
| | 2nd | 2.348 | 2.060 |
| | 3rd | 1.647 | 1.404 |
| | 4th | 1.262 | 1.000 |
| | 5th | 1.00 | 0.713 |
| | 6th | 0.844 | 0.582 |
| | Reverse | 3,863 | 3.168 |
| Final-drive ratio | 3.454 | 3.583 | |
| ELECTRICAL SYSTEM | Alternator | Denso SC2 150 A w/ LIN regulator | Denso SC2 150 A w/ LIN regulator |
| | Battery | Q85 | Q85 |
| SUSPENSIONS | Front | Double wishbone with stabilizer bars | Double wishbone with stabilizer bars |
| | Rear | Multilink with stabilizer bars | Multilink with stabilizer bars |
| BRAKES | Front | Ventilated front disc | Ventilated front disc |
| | Size & Type | Floating type- Disc plate ϕ 280 mm | Floating type- Disc plate ϕ 280 mm |
| | Swept area | 33,9x2 = 67,8 cm ² | 33,9x2 = 67,8 cm ² |
| | Rear | Solid | Solid |
| | Size & Type | Floating type- Disc plate ϕ 280 mm | Floating type- Disc plate ϕ 280 mm |
| | Swept area | 31,5x2 = 63 cm ² | 31,5x2 = 63 cm ² |
| | Power assist | Vacuum booster | Vacuum booster |
| | ABS | Standard | Standard |
| | ESC | Standard | Standard |
| Parking Brake Type | Mechanical (lever type) | Mechanical (lever type) | |
| TIRES | Size & Type | 195/50 R16 3-season 205/45 R17 3-season | 205/45 R17 3-season |
| | Mfr. and model | 16" - Yokohama ADVAN Sport V105 17" - Bridgestone POTENZA S001 | 17" - Bridgestone POTENZA S001 |
| STEERING | Type | Double pinion electric power assist system (DP-EPAS) - rack | Double pinion electric power assist system (DP-EPAS) - rack |

| | | | |
|----------------------------|-------------------------------------|------------|------------|
| | | and pinion | and pinion |
| | Overall Ratio | 15,5 | 15,5 |
| | Turning diameter (curb-to-curb) [m] | 9.4 | 9.4 |
| | Steering turns (lock-to-lock) | 2,7 | 2,7 |
| Performance & Fuel economy | Acceleration 0-100 Km/h [s] | 7.5 | 7,6 |
| | Top speed [Km/h] | 215 | 214 |
| | CO2 [g/km] | 148 | 153 |
| | Combined cycle [l/100Km] | 6.4 | 6.6 |
| | Urban cycle [l/100Km] | 8.5 | 9.1 |
| | Extra Urban cycle [l/100Km] | 5.1 | 5.2 |
| | Emission class | Euro6c | Euro6c |