

ENGINE	Wrangler Sahara 4-door diesel 2.2 ATX 4WD 200 hp
No. of cylinders, layout	4 - in line
Displacement (cm ³)	2143
Bore x stroke (mm)	83.8 x 99.0
Valves per cylinder	4
Compression ratio	15,5:1
Max. power kW @ rpm	147 kW @ 3.500
Max. torque Nm @ rpm	450 Nm @ 2.000
Fuel injection	Diesel Direct Injection Common Rail
Fuel type	DIESEL
Fuel tank capacity (l)	81
UREA tank capacity (l)	18.9
GEARBOX	
Transmission	8-speed AUTOMATIC
1 st	4.714
2 nd	3.143
3 rd	2.106
4 th	1.667
5 th	1.285
6 th	1.000
7 th	0.839
8 th	0.667
Reverse	3.295
Final drive ratio	3.73
DRIVETRAIN	
Transfer case	Command-Trac Low Gear 2.72:1
Crawl ratio	47.8

PERFORMANCE	
Acceleration: 0-100 kph (s)	9,6
Top Speed (kph)	180
CONSUMPTION AND EMISSIONS *	
Emission standard	Euro 6D-Temp
Fuel consumption – urban (l/100 km)	9,7
Fuel consumption – extra-urban (l/100 km)	6,5
Fuel consumption – combined (l/100 km)	7,7
CO ₂ emissions – urban (g/km)	-
CO ₂ emissions – extra-urban (g/km)	-

CO ₂ emissions – combined (g/km)	202
---	-----

** The CO₂ and fuel consumption figures provided were measured using the measurement/correlation method for the NEDC cycle pursuant to Regulation (EU) 2017/1152-1153. The stated CO₂ and fuel consumption figures are not definitive and may evolve further to changes to the production cycle; more up-to-date values will be available at the chosen official FCA dealer.*

WEIGHT AND DIMENSIONS	
Kerb weight STD. A (kg)	2.044
Weight distribution front/rear (%)	52/48
Max payload (kg)	466
Towing capacity (kg)	2495
Height (mm) w/ Standard hard top	1838
Width (mm)	1.894
Length (mm)	4.882
Wheelbase (mm)	3008
Ground clearance (mm)	242
Load capacity (l) with seats in position*	533
Load capacity (l) with flat rear seats*	1.044
*Underfloor cargo volume included	

OTHER	
Approach/departure/breakover angle	35.4/30.7/20
Turning Diameter (m)	12.28
Steering angle (inner/outer angle)	41°/34.4°
Steering Turns	3.24
Steering ratio	14.2
Water Fording (mm/kph)	762/8

2.2L N-S 200CV JL

