

WLTP cycle under approval	NEW E-3008	NEW E-3008	NEW E-3008
MOTOR	ELECTRIC 210	ELECTRIC 320 Dual Motor AWD	ELECTRIC 230 Long Range
Electric motor technology Front / Rear	Synchronous with permanent magnet / -	Synchronous with permanent magnet / Synchronous with permanent magnet 240 (320) cumulated:	Synchronous with permanent magnet / -
Maximum power in kW (or hp)	157 (210) from 4370 to 14000 rpm	157 (210) front from 4370 to 14000 rpm/ 83 (110) rear from 4760 to 14000 rpm	170 (230) from 4740 to 14000 rpm
Maximum torque (Nm)	343 from 250 à 4370 rpm	Front: 343 from 250 to 4370 rpm Rear: 166 from 0 to 4760 rpm	343 from 250 to 4740 rpm

TRANSMISSION

Type	single-speed gearbox	single-speed gearbox	single-speed gearbox
Ratio Front / Rear	9,77 / -	9,77 / 12,396	9,77 / -

BATTERY

Technology	Lithium-ion NMC	Lithium-ion NMC	Lithium-ion NMC
Number of modules/cellules	11/96	NA	NA
Useful Capacity (kWh)	73	73	98
Weight (kg)	520	520	574
Tension (V)	400	400	400

MASSES & CHARGES

Kerb weight (kg)	2114	2199	2174
Maximum braked trailer weight - 12% slope (kg)	1250	1350	1200

PERFORMANCES

Maximum speed (kph)	170	180	170
• 1,000 m standing start	29,7	27,2	29,8
• 400 m standing start	16,5	14,7	16,6
• 0 to 100 kph	8,7	6,4	8,9
In-gear acceleration (seconds)			
• 30 to 60 kph	2,3	1,5	2,3
• 60 to 90 kph	2,8	2,3	2,8
• 80 to 120 kph	5,3	3,9	5,4

RANGE & CONSUMPTION

Range in WLTP combined (km)	525	525	700
Range in WLTP city (km)	NA	NA	NA
Consumption in WLTP cycle - combined (kWh / 100 km)	13,9	13,9	14
Consumption in WLTP cycle - city (kWh / 100 km)	NA	NA	NA
Niveau sonore en mouvement (dB)	NA	NA	NA

CHARGE (20°C from 20% to 80%)

On board charger AC (kW) - Standard/Option	11/22	11/22	11/22
DC maximum Capacity (Kw maxi) - Standard	160	160	160
Charging time Wallbox 11 kW AC (h) On board charger 11 kW	NA	NA	NA
Charging time Wallbox 22 kW AC (h) On board charger 22 Kw	NA	NA	NA
Charging time Super Charger DC (mn)	30	30	27

WHEELS

Type of tyres (standard or option, depending on version)	235/55R19 235/50R20	235/55R19 235/50R20	235/55R19 235/50R20
Spare wheel	Standard: Tire repair kit	Standard: Tire repair kit	Standard: Tire repair kit
Turning diameter between sidewalks (m)	10,6	10,6	10,6

BRAKES & SUSPENSION

Type of front/rear brakes	Front discs: 365x37mm Front Brake Caliper double pistons Rear discs: 356x26mm		
Type of front suspension	Independent wheels - Pseudo-Mac Pherson axle, coil springs and integrated hydraulic dampers, pressurized		
Type of rear suspension	Independent wheels - Multi-link axle, hydraulic dampers, pressurized		

DIMENSIONS (m)

Overall length	4542	4542	4542
Width	1895	1895	1895
Kerb height	1641	1641	1641
Wheelbase	2739	2739	2739
Front overhang / Rear overhang	940 / 863	940 / 863	940 / 863
Front track / Rear track	1630 / 1636	1630 / 1636	1630 / 1636
Ground clearance (mm)	198	198	

BOOT

Boot volume (litres of water) - VDA V210	520	470	520
------------------------------------------	-----	-----	-----

AERODYNAMICS

SCx drag area (m ²)	0,75	0,75	NA
---------------------------------	------	------	----

WLTP cycle under approval