

TECHNICAL SPECIFICATIONS	Alfa Romeo MiTo Quadrifoglio Verde 1.4 TP 170 HP TCT	
SPECIFICATIONS	No. of cylinders, layout	4
	Bore x stroke (mm)	72x84
	Displacement (cm ³)	1368
	Compression ratio	10,0:1
	Maximum power output kW (HP - EC) at rpm (NORMAL)	125 (170) at 5500 rpm
	Peak torque Nm (kgm - EC) at rpm (NORMAL)	230 (23.4) at 2500 rpm
	Peak torque Nm (kgm-EC) at rpm (DYNAMIC)	250 (25.5) at 2500 rpm
	Fuel	Turbocharged by means of exhaust gas turbocharger with engine load management by means of variable intake valve activation
	Stop&Start system for automatic engine stopping/starting for short stops during city driving, useful for optimising fuel consumption and CO ₂ emissions	Standard
TRANSMISSION	Drive	Front
	Transmission	Twin clutch
TYRES	Standard trim level	215/45 R17
SUSPENSION	Front	MacPherson
	Rear	Torsion beam
BRAKES	Front (mm)	305
	Rear (mm)	251
DIMENSIONS	Wheelbase (mm)	2511
	Length / width (mm)	4063/1720
	Height (mm)	1446
	Track (mm)	1483/1475
	Luggage compartment capacity (dm ³)	270
	Overhang	904
CAPACITIES - WEIGHTS	Fuel tank (litres)	45

	Kerb weight (kg)	1170
	Max. towable weight (kg) braked	500
PERFORMANCE	Max. speed (km/h)	219
	Acceleration (1 person + 30 kg) 0-100 km/h (s)	7.3
FUEL CONSUMPTION - EMISSIONS as per directive 1999/100/EC	Urban cycle consumption (l/100 km)	7.0
	Extra-urban cycle (l/100 km)	4.4
	Combined cycle (l/100 km)	5.4
	CO ₂ emissions (g/km)	124
	Environmental classification	Euro 6